

FOR HOOD CLEANERS

Proper Care For Grease Guard During Hood Cleaning



GREASE GUARD®

Rooftop Defense Systems®

G2® Grease Guard® Rooftop Defense Systems® are designed to collect the grease that leaks from rooftop kitchen exhaust fans. To prevent the premature saturation of the Grease Guard filter with grease and chemicals, the unit **MUST** be covered prior to having your kitchen exhaust system professionally cleaned.

Kitchen exhaust cleaning chemicals will greatly reduce the ability of the filter to absorb grease and may cause it to disintegrate.

If the Grease Guard unit is not properly covered during the cleaning process, and therefore becomes saturated with excess grease and chemicals, the cost of the replacement filters and the additional service may become your responsibility.

To protect the Grease Guard unit, please ask your kitchen exhaust cleaning crews to follow these four simple steps:



Cover the entire unit with plastic prior to cleaning the kitchen exhaust system.



Empty grease catch pans into a separate container – not into the Grease Guard unit.



Clean the rooftop during the kitchen exhaust cleaning process.



When the job is complete, **Remove** the plastic from the Grease Guard unit.

Your cooperation in communicating this important information to the company cleaning your kitchen exhaust system is greatly appreciated. Following these simple steps will extend the life of your Grease Guard® Rooftop Defense Systems®.

Thank YOU!

Question not answered?
Give us a call or visit us!



1-800-913-7034
www.greaseguard.com